

Units 1-3 Nisbet
Way
Ravenstruther
Lanark
ML11 7LT

Call: 01555 870003



Technical specifications:

Deluxe

Product Name	:	Deluxe	
Application	:	Lawns, patios, swimming pool surround etc.	
Production process	:	Tufted cut pile	
Pile material	:	100% PE monofilament	
Yarn Dtex	:	13.400 Dtex / 16 ply	
Quality	:	100% European product, free of heavy metals and toxics.	
Primary Backing	:	100% PP, UV stabilised, approx 135 gr./m2	+/- 10%
Coating	:	SBR latex, approx 840 gr. / m2	+/- 10%
Waterpermaebility	:	> 300 ml per minute per 100 cm2	
Pile height	:	approx. 30 mm	+/- 10%
Total height of construction	:	approx. 32 mm	+/- 10%
Pile Weight	:	approx. 1490 gr./m2	+/- 10%
Total weight of construction	:	approx. 2465 gr./m2	+/- 10%
Tuftgauge	:	3/8' gauge	
Stitches per linear metre	:	140	+/- 10%
Stitches per square metre	:	14.700	+/- 10%
UV stability	:	7 years warranty in Northern Europe	
	:	6 years warranty in Southern Europe	
Lightfastness	:	Bluescale 1-8 > 7 (according DIN 54004)	
Colourfastness	:	Greyscale 1-5 >4 (according DIN standard)	
Installation method	:	Loose laid on bound or unbound subbase	
Infill	:	Silica sand, gradation 0,5 - 1,0 mm	
Sandtype	:	min. 80% round of shape	
Recommendation	:	approx. 5 kg per m2 for stabilisation	
Roll width	:	2 or 4 metres	+/- 1%